

220 kV BRACED INSULATE /ERS 132 -



BONOMI ENERGY


references since 2000



FOCUS ON OUR PRODUCTION	2
QUALITY CONTROLS	4
RED ELECTRICA DE ESPAÑA	6
TERNA SPA	10
RETE FERROVIARIA ITALIANA	14

HOW OUR INSULATORS ARE MADE

In the **1950s Rebosio** is among the first companies in Europe to introduce **Teflon** for the production of insulators, as an alternative to ceramics and glass. In the 1960s and 1970s **significant investments were made in research and development** to **improve the material**, while in the 1980s Rebosio strengthened with the standardization of the raw material: **HCR/LSR SILICONE**. Both these options are subjected to a high temperature vulcanization process (HTV). In the same period, Isoelectric also introduced the use of silicone for the production of insulators.



MECHANICAL CHARACTERISTICS

The high quality of the fiberglass core and of the terminals their correct sizing allow, through an adequate mechanical compression, to obtain an intimate contact that ensures the mechanical seals that is required by international standards.

ELECTRICAL CHARACTERISTICS

The high electrical performance of our insulators is given by three key factors, on which the technical energy office invests great attention:

- chemical stability of the cover;
- · control of the electric field;
- hydrophobicity of the cover.

LONG DURATION

Our Isolflon-E insulators have been operating on various lines for over 40 years. We have tested some lots to determine their status after years of activity here are the results:

- the inspected insulators showed no mechanical or electrical changes;
- housing materials tend to regenerate from high environmental pollution;
- there was very high resistance to erosion and trace;
- the high quality of Bonomi's mixture allows the water repellent property of the insulator to be kept constant over time.

CONTINUOUS CONTROLS

We carry out continuous quality controls across the finished products and the raw materials according to the instructions of the Quality Plan.

COMPLETE TRACEABILITY

Certificate of origin of each raw material

Production parameters used during the process

Test effectuated during the production

Final acceptance test on the finished product



GRUF	PPO SP Palasta Cal				PR	ODUCTION C	ONTE	ROL F	PLAN			PFC	N°	2018	8-E0XXXX RE	V. 1.00	
EB Rebosio S.r.l. Progettazione e componenti per zistenu		INT.REF OF 17-dic-18							CUSTOME -		ORDER		• OF				
B	BONOMI di trazione elettrica Isolatori compositi		Issued by:		Date	Verified by: Date			Date	Sent to:	Date	$\overline{}$		mer approval:	Date		
۶F	Società del Gruppo Bonomi		- RMILANI	7/1 -	17/12/18	A.CAMPANELLA/ 17/12/18				17/12/18							
•			Robers Klang			lem joulle for											
MANUFACTURER SITE EB REBOSIO SRL			TENSION INSULATOR	E EBR DWG							INTERNAL DWG RE		:		CUSTOMER DWG REV.	OF -	
MANUFACTURE & CONTROL PHASE OF THE PROCESS (*)		(*)	REFERRING DO	DCUMENTS		CONTROL/TEST				CONTROL	ERFORM	ERFORMED BY:		OUTPUT			
		CONTRACTUAL ACCEPTANCE DOCUM. CRITERIA	PROCEDURE AND INTERNAL DOCUM.		EQUIPMENT	100%		SAMPLE	METOD	EB REBOSIO (1) C	USTOMER	R (1)		RECORDING DOCUMENTS			
1 C	HECK IN ENTRANCE OF END-FITTINGS AND INSUL	ATO		IN LENGT	L DOCOM.												
1.1	Control of congruency packing list - goods	1	PACKING LIST	IST 202		-	х			IST 202			TT				
1.2	Control of congruency packing list - purchase order	1	PURCHASE ORDER				X				LG WAREHOUSE						
1.3	Control of the origin certific and/or supplier test report	1					X			IST 150	cq QUALITY		++		ORIGIN CERTIF. APPROVI	ED-TEST REP.	
1.4	Testing of goods entered inwards	h	REF. STANDARDS	DIS/PCQ	TOXXXX	(3)		(3)	every batch	PCQ	CONTROL		++		COMPUTER SYS	TEM	
	HECK IN ENTRANCE OF FIBERGLASS RODS	_				1-7		1-7									
2.1	Control of congruency packing list - goods	Ti	PACKING LIST			-	х						ТТ				
2.2	Control of congruency packing list - purchase order	h	PURCHASE ORDER	IST	202		X			IST 202	LG WAREHOUSE				•		
-	Control of the origin certific and/or supplier test report	t	STF	IST	150		X			IST 150	CQ QUALITY		++		ORIGIN CERTIF. APPROV	D-TEST REP.	
_	Dielectric Rigidity following fiber direction	H.	IEC 60243		-	Dielectric Rigidity		(3)		101 100	CONTROL		++		SUPPLIER		
_	Dye penatration test	!	IEC 62217 § 9.4.1		Mechanic	tester		(3)		IST 156					COMPUTER SYSTEM		
_	Mechanical compression test	!	EC 02217 9 9.4.1			Mechanical testing			every batch								
_		<u> </u>	-	ļ		machine 200 kN Mechanical testing		(3)			cq QUALITY CONTROL						
_	Mechanical tensile test (max SML)	<u> </u>	IEC 61109	PCQ	BARRA V/R	machine 1000 kN		(3)									
_	Bending Strength at Heating Conditions 90°C	1	-			Mechanical testing machine 200 kN	(3)	(3)									
2.9	Bending Strength at Heating Conditions 150°C	1	-			Digital Thermometer		(3)									
2.10	Stress corrosion test -Damage proof limit 96h (1 mol / 1HNO3 al 67% Stress)	1				Load cell		(3)									
2.11	Verification of dimensions	1				flexible meter Caliber		(3)									
3 CH	HECK IN ENTRANCE OF SILICON RUBBER, PRIMER			•		Caliber				•							
3.1	Control of congruency packing list - goods	1	PACKING LIST				X										
3.2	Control of congruency packing list - purchase order	1	PURCHASE ORDER	161	202		X			IST 202	LG WAREHOUSE						
3.3	Control of the origin certific and/or supplier test report	1	STF	IST	150	-	X			IST 150			\top		ORIGIN CERTIF. APPROVI	ED-TEST REP.	
3.4	Tracking strength	1	IEC 60587			Apparatus according to IEC 60587		(3)			1				OUTLER		
3.5	Density	1	ISO 2781	1		Analytical Balance		(3)									
3.6	Hardness Shore A	ħ	IEC 62217	1	PCQ SILICONE Med	SILICONE	Hardness Tester		(3)	1 batch for		CQ QUALITY CONTROL					
3.7	Verification of Tensile Strength	I/E	ISO 37	PCQ SILICONE			(Shore A)		supplier each month	IST 157	CONTROL				COMPUTER SYS	TEM	
_	Verification of Elongation at breaking	-	ISO 37			Mechanical testing		(3)									
_	Verification of Tear Strength	-	ISO 34-1			machine 2 kN		(3)									
_	ND-FITTINGS ASSEMBLING	100	100 04 1					(3)									
	Assembling on F/W rod	L			OT								T T				
-	Control at the beginning of production	ti			250	(4)		1° p	ocs.								
_	Tensile Mechanical Test at SML for beginning of production (2)	1		DIS. EOXXXX		Mechanical testing		1° p		IST 250	RPI INSULATOR				COMPUTER SYS	TEM	
	Visual Check on line	1	IEC 61109 § 13.2			machine 1000 kN	x				DPT.						
		1											\perp		Dec 4		

GRUPPO EB Rebosio S.r.I.					PR	ODUCTION (CONT	ROL PLAN				PFC N	N°	201	8-E0XXXX	REV.	1.00
Progettazione e componenti per sistenu di trazione elettrica	١.	INT.REF OF 17-dic-18 CUSTOME -									(ORDER	-	OF	-		
BONOM Isolatori compositi	-		Issued by:		Date	Verified by: Date				Sent to:		Date		Custo	omer approval:		Date
(B) CEDOSIO	ł	Robe	So K	Da.	7/12/18	- Com ja	.CAMPAI	NELLA/La-	17/12/18						•		
ANUFACTURER SITE EB REBOSIO SRL		PRODUCT DESCRIP	TION	R EBR DWG						E0XXXX		REV. OF			CUSTOMER DWG	REV.	OF •
MANUFACTURE & CONTROL PHASE	(*)	R	EFERRING DO	CUMENTS			CO	NTROL/TEST		CON	NTRO	OL PERFORMED	PERFORMED BY: OUTPUT				
OF THE PROCESS		CONTRACTUAL DOCUM.	ACCEPTANCE CRITERIA			EQUIPMENT 100% SAMPLE		METOD	EB REBOSIO (1) CUS		CUSTOMER	OMER (1)		RECORDING DOCUMENTS		ENTS	
5 SHEDDED HOUSING MOULDING	_	DOCOM.	GRITERIA	INTERNAL DO	OCOM.												
5.1 Primerization	1										Г		П				
5.2 Moulding of the shedded housing	Т			DOT-IST 2	260						T				1		
5.3 Control at the beginning of production	1					(4)		1° pcs.			T				COMPUTER SYSTEM		
5.4 Check of adesion	1							1 pc. each shift									
5.5 Verification of silicon rubber thickness on rod	1							2 pcs. each shift	IST 260	RPI INSULATOR							
5.6 Verification of silicon rubber compactness (absence bubbles)	1			DIS. E	0XXXX	Ultrasonic Device		1 pc. each hour		Dr I.							
5.4 Visual Check on line	1	EC 61109	§ 13.2				х										
6 END-FITTINGS COMPRESSION	_										_						
6.1 Compression of the end-fittings	1										Π						
6.2 Control at the beginning of production	1			DOT		(4)		1° pcs.			Т				COMPUTED O		CTEM
6.3 Visual Check on line	1 1	EC 61109	§ 13.2	IST 250			X		IST 250	RPI INSULATOR					COMPUTER SYSTEM		И
6.4 Tensile Mechanical Test at SML	1					Mechanical testing machine 1000 kN		1% for batch ≤300pcs. 0.5% for batch>300pcs.		511.							
7 INDIVIDUAL CHECK, LABELLING																	
7.1 Tensile Mechanical Test at 0,5xSML	1.1	EC 61109	§ 13.1	DOT		Mechanical testing machine 1000 kN	X		IST 270	RPI INSULATOR	Π						
7.2 Visual Check	1 1	EC 61109	§ 13.2	IST 270			X		151 270	DPT.					COMPUTER SYS		STEM
7.3 Labelling-Marking	1	EC 61109	§ 5.	DIS. EOX	OXXX												
8 SAMPLE TESTS																	
8.1 Identification of isolators	1		-														
8.2 Visual examination	1		§ 12.2														
8.3 Verification of dimensions	ı	IEC 61109	§ 12.2	IST 280		flexible meter Caliber go/not go gauge		1 se n<50 2 se 50 <n<300< td=""><td>PCQ IST 280</td><td>cq QUALITY CONTROL</td><td></td><td></td><td></td><td></td><td>TEST</td><td>REPORT</td><td></td></n<300<>	PCQ IST 280	cq QUALITY CONTROL					TEST	REPORT	
8.4 Verification of the looking sistem (2)	1		§ 12.3			Mechanical testing machine 2 kN		CEI EN 61109 se n>300	101 200	CONTROL							
8.5 Verification of the SML	1		§ 12.4			Mechanical testing machine 1000 kN		1									
8.6 Galvanizing test	1		§ 12.5	DIS./PCQ E0X	OOX	Thickness tester		1									
9 PACKING	1			IST 290													
0 FINAL INSPECTION	1										Г						

his planning document does not present the results of the facts. The results of tests performed during various stages of control mentioned in the PFC are recorded in documents at the last column in the PFC and are available at the EB Rebosio S (*CQC Quality Control Plan - DIS = Drawing - IST=Work Instruction - DOT= Production Order

Thoraction - DOT = DOT =


as prescribed by internal PCC
 as prescribed by IST 220

RED ELECTRICA DE ESPAÑA

Over 1,300 energy braced insulated cantilevers – single and double

Bonomi, through the Spanish distributor
Disace Energía, has supplied more than 1,300
132 kV energy braced insulated cantilevers
for T&D (both single and double) which
have been installed on the island of
Fuerteventura, Spain.

The project, that ended in May 2018, was the result of a close consultancy driven cooperation between **Bonomi**, our distributor and **Red Electrica De España**, the electricity company responsible for the project.



Wet power frequency voltage test led by EGU

Together we evaluated **specific leakage distance** to be applied to all provided insulators (50mm each kV) to ensure greater insulation performances and highlight the strong climate resistance of our products in the Canary Islands which is a land where there are **strong winds and high levels of air salinity**.







Bonomi's braced insulated cantilevers on some trellis in Fuerteventura, Spain









L 1029

HIGH VOLTAGE TESTING LABORATORY

Accredited testing laboratory No.: 1029 Accredited by Czech Accreditation Institute according to ČSN EN ISO/IEC 17025:2005

TEST REPORT No.: 10696/A/17

CUSTOMER:

EB Rebosio S.r.L. Via Carso 49 24040 Madone

Italy

TEST OBJECT:

Braced line post assembly

TYPE SPECIFICATION: N/A

TEST STANDARDS:

IEC 60383-2 Ed.1:1993, IEC 60060-1 Ed.3:2010

Michal Novotný Test engineer

Testing Laboratory

Jan Bolech Head of High Voltage Jan Lachman, Ph.D.

Director of EGU - HV Laboratory a. s.

Test report is confidential and must not be passed over or transferred to any third party without written approval of the customer. Test results relate only to the tests given in presented report and do not substitute any other documents. The report shall not be reproduced except in full without written approval of the festing laboratory.

Copies: 1+1

Pages: 10

Date: 2017-09-13

Klokner Institute CTU in Prague

Tel: +420 224 353 537

CZECH TECHNICAL UNIVERSITY IN PRAGUE

Klokner Institute

Šolínova 7, 166 08 Prague 6 Czech Republic



Test report

Number of report

146/16/EXPO

Date Number of pages 9th December 2016 11

Order No.

16 00 J 152

Customer

EB Rebosìo Srl - Gruppo Bonomì Isolatori e accessori per linee elettriche e

ferroviarie Via Carso, 49 - 24040 Madone(BG

ITALY

Subject of test

Tensile test of Braced Line Post Assembly 132 kV

Manufacturer

EB Rebosio Srl - Gruppo Bonomi

Drawing No.

G00556, ED. 4

Test standard

customer specification

Copies/No. of copy

4/1 2 3 4

Responsible engineer

Tomáš Jaterka


Co-operation Head of laboratory Michal Křesťan, MSc.


Jiří Kolísko, Ass. Prof., Ph.D., MSc.

Director of Kl CTU

Jiří Kolísko, Ass. Prof., Ph.D., MSc.

1 from 11





TERNA SPA
ITALY

Over 500 energy braced insulated cantilevers – double

Terna S.p.A. is a transmission system operator (TSO) based in Rome, Italy. It operates through Terna Rete Italia, that manages the Italian transmission grid and Terna Plus which is in charge of new business opportunities and non-traditional activities in Italy and abroad. With around 98% of the Italian high-voltage power transmission grid, Terna is the first independent electricity transmission grid_operator in Europe and one of **Bonomi**'s most important customers.

Since 2000 we have actually **supplied more than 500 220 kV double energy braced insulated cantilevers** to be installed all over Italy and Europe.



Bonomi's braced insulated cantilevers on some Terna's trellis in Italy



TO WHOM IT MAY CONCERN

Rome, April 20th 2017

Object: PERFORMANCE CERTIFICATION

We declare that EB REBOSIO srl, with registered office in Montichiari (BS) via A. Mercanti 17 n.25018, has supplied over the last five years insulators made of composite material 150, 220 and 380 kV under the contracts number:

- 6000001869 of 9/7/2013
 - · 6000001995 of 25/3/2014
 - 6000002097 of 26/11/2014
 - 6000002230 of 19/10/2015
 - 6000002231 of 19/10/2015

We certify that the above insulators have been installed throughout the national territory to our satisfaction without the presence of any criticality.

Yours faithfully

Senior Manager Purchasing & Sourcing Overhead and cable line Giuseppina SCACCIA SCARAFONI



Spett.le EB Rebosio S.r.l. Via Carso nº 49 24040 Madone (BG)

C. Att.ne: Sig. Giovanni Giobbe

Milano, 20 Giugno 2019

Ns. Rif. 19.16463

Oggetto: Certificazione di prodotto degli isolatori compositi per distanziatori Interfase tipo J20 (documento TERNA LIN_00000J20 Rev. 00 del 27/07/2018)

Con la presente Vi confermiamo che le prove legate alla certificazione degli isolatori per distanziatori interfase tipo J20 (rif. documento TERNA LIN_00000J20 Rev. 00 del 27/07/2018 e lettera TERNA /P2019-0010411 – 07/02/2019), previste dalle seguenti specifiche:


- TERNA LIN_00000J20 Rev. 00 del 27/07/2018
- TERNA LIN_00000J39 Rev. 00 del 24/04/2013 TERNA PT500ST Rev. 02 del 21/11/2007
- Comunicazione TERNA/P2019/0044045-19/06/2019


sono state completate, come da programma temporale EB REBOSIO del Gennaio 2019 e successiva integrazione del Maggio 2019, con esito positivo e a complemento del Dossier di certificazione sarà emesso il relativo Certificato di Conformità

Cogliamo l'occasione per inviare cordiali saluti.

SGS Italia S.p.A. Industrial Services
On behalf of Business Manage

SGS Italia S.p.A. Via Caldera, 21 - 20153 Milano - Italy I + 39 02 739 31 I + 39 02 701 24 630 e sgs.italy@sgs.com www.sgsgroup.it





RFI ITALY

Over 1,000 energy braced insulated cantilevers single and double | normal and anti-salt insulation

Rete Ferroviaria Italiana (RFI) is
the Italian railway infrastructure manager and
owner of Italy's railway network. It provides
electrification, signalling, maintenance and
other services for the railway network.

Bonomi have been dealing with the
electrification process of Italian railways
since the very beginning: that is why RFI
represents today a very prestigious client for
our Group.

Since 2000 we have been supplying to RFI more than **1,000 150 kV energy braced insulated cantilevers** which have been used to electrify the most modern Italian routes.



Our energy braced insulated cantilevers installed on some trellies in Italy





Standard Teenologici e Sperimentali Standard Energia

Oggetto: Referenze "Gruppo Bonomi di Montichiari (BS).

Hereby I declares that **BONOMI EUGENIO Spa - EB REBOSIO Srl** (Companies of GRUPPO BONOMI) is our usual supplier for supplying of material for overhead contact lines as:

- Droppers and clamp for droppers; Cantilevers (Aluminium Type); Tensioning devices with Pulleys;

- Composite insulators and components for section insulators.

The products are installed on RFI network since several years and their products performed until today has been successful.

The above products are also located in areas with wide variety of climatic conditions and industrial areas with both clean and polluted atmosphere.

Best wishes

Pag. 1 di 1

EGÚ-HV LABORATORY 190 11 PRAGUE 9 - BECHOVICE

ACCREDITED TESTING LABORATORY No.: 1029

CUSTOMER: ABB Sae Rebosio srl

ORDER NO: 990315 DATE OF TEST: August 11th- November 3rd, 1999 TEST NO: 8514/D/99

TEST REPORT No: 37012184/D

Composite Post Insulator TEST OBJECT: TYPE SPECIFICATION: DRAWING No: E00764 MANUFACTURER: ABB Sae Rebosio srl TEST STANDARD:

IEC 1109: 1992, IEC 60-1:1989 ESB - PG404-S21

PAGUE

HEAD OF THE TEST: DIRECTOR OF HV LABORATORY:

Václav Sklenička & Jonko Totev


of flery COPIES: 4


Jaroslav Vokálek PAGES: 24


Test report is determinated for service application only. Further use solely with approval of the customer. Test results relate only to the tests given in presented report and do not substitute any other documents. The report shall not be reproduced except in full without written approval of the testing laboratory.

In Prague 9 -Běchovice: December 10th, 1999













هيئة مياه وكهرباء أبوظبمي Abu Dhabi Water & Electricity Authority





الشركة العُمانية لنفل الكهرباء ش.م.ع.م OMAN ELECTRICITY TRANSMISSION COMPANY S.A.O.C









































Notes



